

Technical Accessory Guides (TAGs)

For Associates, Resellers, ISVs and Alliance Partners Global



Version: Active-Only Will only show products that are known to be available for sale

Need to provide an update or change? Contact <u>mailto:pgw786@zebra.com</u>





For Internal Use by PartnerConnect Members Only

Proprietary and Confidential. ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©Zebra Technologies Corp. and/or its affiliates. All rights reserved.



TC73/TC78 Series Technical Accessory Guide



Does not include TC70/TC72/TC75/TC77 accessories. See separate guide for these TC7X series accessories.

NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.

* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Cradles and Charging

Single Device Cradles				
Part Number	Picture	Description	Notes	Required Items
CRD-NGTC7-2SC1B		Single Slot Charge-Only ShareCradle KIT	 Will charge TC73/TC78 and a spare battery. Will charge standard size battery in device from 0.80% in as little as 1.5 hours Compatible with devices units with hand strap or Trigger Handle attached. Kit includes: Single Slot Charge-Only Cradle (CRD-NGTC5TC7-2SC1B) Power Supply (PWR-BGA12V50W0WW) DC Line Cord (CBL-DC-388A1-01) shim for device (SHIM-CRD-NGTC7) Connects to charge contacts on bottom of device. 	► AC Line Cord (23844-00-00F or country specific version)
CRD-NGTC7-2SE1B		Single Slot USB/Charging Cradle KIT	 Will charge TC73/TC78 and a spare battery. Will charge standard size battery in device from 0-80% in as little as 1.5 hours Compatible with devices units with hand strap or Trigger Handle attached. Kit includes: Single Slot USB/Charging Cradle (CRD-NGTC5TC7-2SE1B) Power Supply (PWR-BGA12V50W0WW) DC Line Cord (CBL-DC-388A1-01) shim for device (SHIM-CRD-NGTC7) Connects to charge contacts and USB-C port on bottom of device. Can be enhanced to provide Etherne communications by installing USB to Ethernet Module (MOD-MT2-EU1-01). 	 AC Line Cord (23844-00-00F or country specific version) For USB communication: Micro USB Cable (25-124330- 01R)

	1	1		
CRD-NTC7X-1SNWS-01		Workstation Connect Cradle	 An enhanced single-slot charging cradle allowing users to use the TC73/TC78 as a workstation or kiosk. Cradle includes the following additional ports: HDMI Ethernet 4 USB ports for keyboard, mouse, and other supported USB devices. Connects to I/O connector on rear of device. Cover on rear of cradle can be secured using screw to prevent unauthorized access to ports. Not compatible with snap-on accessories. 	 Power Supply (PWR-BGA12V50W0WW) DC Line Cord (CBL-DC-388A2-01). CBL-DC-388A1-01 may also be used, but CBL-DC-388A2-01 is recommended to provide easier installation of peripheral cables and the cradle's port cover. AC Line Cord (23844-00-00F or country specific version)
MOD-MT2-EU1-01		USB to Ethernet Module	 Attaches to USB/Charging ShareCradle (CRD-NGTC5TC7-2SE1B) to provide Ethernet support Mechanical switch selects between USB B port and RJ45 Ethernet jack. 10/100/1000 Mbps speed LEDs on module indicate connectivity and speed. 	USB/Charging ShareCradle Kit (CRD-NGTC5-2SE1B)
Multi-Device Cradles				
Part Number	Picture	Description	Notes	Required Items
CRD-NGTC7-5SC5D		5-Slot Charge-Only ShareCradle KIT	 Will charge up to five devices. Will charge standard battery in device from 0-80% in as little as 1.5 hours. Does not charge spare batteries Compatible with devices with hand strap or Trigger Handle attached. Kit includes: S-Slot Charge-Only Cradle (CRD-NGTC5TC7-SCSD) Power Supply (PWR- BGA12V108W0W) DC Line Cord (CBL-DC-381A1-01) shim for device (SHIM-CRD-NGTC7) - QTY 5 Can be racked/ mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD- SMRK-01) Connects to charge contacts on bottom of device. 	► AC Line Cord (23844-00-00F or country specific version)

CRD-NGTC7-5SC4B	5-Slot Charge-Only ShareCradle with Spare Battery Charging slot KIT	 Will charge up to four devices and four spare batteries. Will charge standard battery in device from 0-80% in as little as 1.5 hours. Compatible with devices with hand strap or Trigger Handle attached. Kit includes: 5-Slot Charge-Only ShareCradle with Spare Battery Charger (CRD-NGTC5TC7-5SC4B) Power Supply (PWR-BGA12V108W0WW) DC Line Cord (CBL-DC-381A1-01) shim for device (SHIM-CRD-NGTC7) - QTY 4 Can be racked/ mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01) Connects to charge contacts on bottom of device. 	► AC Line Cord (23844-00-00F or country specific version)
CRD-NGTC7-5SE5D	5-Slot Ethernet/Charging ShareCradle KIT	 Allows network speeds up to 1 Gb Will charge standard battery in device from 0-80% in as little as 1.5 hours. Does not charge spare batteries Compatible with devices with hand strap or Trigger Handle attached. Kit includes: 5-Slot Ethernet+Charge Cradle (CRD-NGTC5TC7-5SE5D) Power Supply (PWR- BGA12V108W0WW) DC Line Cord (CBL-DC-381A1-01) shim for device (SHIM-CRD-NGTC7) - QTY 5 Can be racked/ mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD- SMRK-01) Connects to charge contacts and USB-C port on bottom of device. 	
BRKT-SCRD-SMRK-01	5-Slot ShareCradle Mounting Bracket	 Allows for rack and wall mounting of one 5-Slot ShareCradle, up to four Single Slot ShareCradles, or up to four 4-Slot Battery Chargers. Bracket can be mounted on standard 19" network rack or on a wall. Has cable routing slots and removable power supply tray that stores and conceals power supplies. Adjustable tabs & screw mounts for easy hanging/installation. Adjustable orientations: - 25° High Density (5-Slot Charge Only Cradle) Horizontal (Single Slot Cradle or 4- Slot Battery Chargers). See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket. 	

ADP-TC7X-PLT-FX		5-Slot ShareCradle Mounting Bracket Adapter Plate for Honeywell	 Allows Zebra Multi-Slot ShareCradles to be mounted on legacy Honeywell Flex Cradle Wall Mount Brackets (HON SKU #203-641-002). Includes hardware to attach plate to HON wall bracket and secure ShareCradle to plate. NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
Misc. Cradle Accessories				
Part Number	Picture	Description	Notes	Required Items
CRDCUP-NGTC7-01 (single cup) CRDCUP-NGTC7-05 (set of 5 cups)		TC73/TC78 Charge-Only ShareCradle Cup Conversion Kit	 Can be used to replace a legacy TC7X series cradle cup when migrating from legacy TC7X to TC73/TC78. Can also be used to replace a damaged cradle cup or to create a multi-slot cradle supporting a mixed combination of devices (i.e. two TC21/TC26 and three TC73/TC78). Only compatible with cradles that use ShareCradle design (i.e. TC5X series). Kit includes: Charge-Only ShareCradle Cup (CRDCUP-NGTC5TC7) shim for device (SHIM-CRD-NGTC7) screw for attaching cup to cradle 	
CRDCUP-NGTC7ETH-01 (single cup) CRDCUP-NGTC7ETH-05 (set of 5 cups)		TC73/TC78 USB + Charge ShareCradle Cup Conversion Kit	 Can be used to replace a legacy TC7X series cradle cup when migrating from legacy TC7X to TC73/TC78. Can also be used to replace a damaged cradle cup or to create a multi-slot cradle supporting a mixed combination of devices (i.e. two TC21/TC26 and three TC73/TC78). Only compatible with cradles that use ShareCradle design (i.e. TC5X series). Kit includes: Charge + USB ShareCradle Cup (CRDCUP-NGTC5TC7ETH) shim for device (SHIM-CRD-NGTC7) screw for attaching cup to cradle NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
SHIM-CRD-NGTC7	TC73/76	Replacement ShareCradle Cup Insert/Shim (1 shim)	 Replacement cradle insert/shim that are typically included with each TC73/TC78 ShareCradle. Order to replace lost/damaged shims or when swapping legacy TC7X cradle cups for TC73/TC78 cups (also requires CRDCUP-NGTC5TC7) or when migrating from TC53/TC58 to TC73/TC78. Black color 	
Battery Charging				
Part Number	Picture	Description	Notes	Required Items

SAC-NGTC5TC7-4SCHG		4-Slot Battery Charger	 Charges up to four spare Standard capacity or Extended capacity batteries Standard capacity batteries will charge from 0-90% in about 4 hours Can be used standalone or up to 4 Chargers can be mounted on Mounting Bracket (BRKT-SCRD-SMRK-01) 	► Power Supply (PWR-
SAC-NGTC5TC7-4SCHG-01		4-Slot Battery Charger Kit	 Charges up to four spare Standard capacity or Extended capacity batteries Standard capacity batteries will charge from 0-90% in about 4 hours Kit includes: 4-Slot Battery Charger (sAC-NGTC5TC7-4SCHG) Power Supply (PWR-BGA12V50W0WW) DC Line Cord (CBL-DC-388A1-01) Can be used standalone or up to 4 Chargers can be mounted on Mounting Bracket (BRKT-SCRD-SMRK-01) 	► AC Line Cord (23844-00-00F or country specific version)
BTRCUP-NGTC5TC7-01		4-Slot Battery Charger Conversion Kit	 Used to replace a legacy TC7X series Battery Charger on a Multi-Slot ShareCradle when migrating from legacy TC7X to TC73/TC78. Please Note: When replacing legacy TC7X Battery Charger on Multi-Slot ShareCradles the 4-Slot Battery Charger Adapter Cup must also be removed 	
Direct to Device Charging				
Part Number	Picture	Description	Notes	Required Items
CBL-TC5X-USBC2A-01 or CBL-TC2Y-USBC90A-01		USB-A to USB-C cable	 USB-A to USB-C cable Attaches to USB-C port on bottom of device Cable length is 1M (~3.25 ft.) CBL-TC2Y-USBC90A-01 features USB-A connector with a 90° bend allowing cable to be used in tighter locations. Cable length is about 1.1M (45"). 	
Communication Cables				
Part Number	Picture	Description	Notes	Required Items

CBL-TC5X-USBC2A-01 or CBL-TC2Y-USBC90A-01		USB-C cable	 USB-A to USB-C cable Attaches to USB-C port on bottom of device. Cable length is 1M (~3.25 ft.) CBL-TC2Y-USBC90A-01 features USB-A connector with a 90° bend allowing cable to be used in tighter locations. Cable length is about 1.1M (45"). Can be used with USB Cigarette Lighter Adapter (CHG-AUTO-USB1-01) for in-vehicle charging. 	
3rd party *		USB-C cable	► Attaches to USB-C port on bottom of device.	
25-124330-01R	0	Single Slot Cradle to PC/Host USB cable	 Used with Single Slot USB/Charging Cradle Micro USB connection on cradle end Cable length is 48 inches 	
Snap-On Accessories				
Part Number	Picture	Description	Notes	Required Items
TRG-NGTC7-ELEC-01		Trigger Handle	 Uses electrical trigger via contacts on back side of TC73/TC78. Trigger Handle accessory offers customers the option of using the product in a gun form factor, ideal for scan-intensive situations. Does not block access to rear facing camera and flash allowing camera to be used while using the trigger handle. Compatible with both Standard and Extended capacity batteries Optional Wrist Strap (SG-PD40-WLD1: 01) also available. 	

Mobile Payment (mPOS)				
Part Number	Picture	Description	Notes	Required Items
PD20 (various SKUs)		PD20 Payment Device	 Attaches to back of TC73/TC78 allowing the device to accept payment cards. Equipped with NFC, Chip and MSR readers. Certifications include: PCI-PTS 6 SCR and SCRP EMV L1 EMV L2 (Contact and Contactless for Visa, Mastercard, American Express, Discover, China UnionPay, and Interac). 	► Battery with Payment Support (BTRY-NGTC5TC7- PYMT)
Soft Goods - Cases/Hols	ters			
Part Number	Picture	Description	Notes	Required Items
SG-NGTC5TC7-HLSTR-01		Soft Holster	 Vertical orientation with Open Bucket design to accommodate TC73/TC78 or device with optional Trigger Handle. Strap on rear of holster allows adjustment for use with the accessory options mentioned above. Leather material. Includes Loop for storage of optional stylus. Non rotating for maximum durability. Holster includes cut-out for speaker output. 	
AK4337DW (3rd party) * http://www.ultimacase.com	LIC.	Ultima Case Rugged Holster with Fixed Belt Loop	 Durable, easy-care Ballistic Nylon exterior. Ruggedized for long-lasting durability. Fixed belt loop for up to 2" waist belt. Bottom vent for quick insertion of device. Large pockets on sides for markers, pens, etc. Easy-in, easy-out access to device fo fast-paced scanning. RoHS and REACH compliant. 	

Vehicle Cradles and Powered Cradles and He	A contract of the series of th	Wrist Strap for Ingger Handle	► Attaches to bottom of Trigger Handle (TRG-NGTC7-ELEC-01) 3	
Vehicle Cradles and	Holders	Wrist Strap for Trigger Handle	(TRG-NGTC7-ELEC-01)	
	A Constraint of the second sec	Wrist Strap for Trigger Handle	(TRG-NGTC7-ELEC-01)	
- NO Sin Sin	2	Wrist Strap for Trigger Handle		
SG-PD40-WLD1-01	$\left \left(\right)\right $			
SG-NGTC5TC7-HDSTP-0 (single strap) SG-NGTC5TC7-HDSTP-0 (pack of 3) SG-NGTC5TC7-HDSTP-1 (case of 1000) NOTE: 1000 count case is a custo product. Please work with your Ze representative to open a Custom P Request (CPR) if you would like to this item.	K m abra roduct	Hand Strap	 Allows device to be easily held in pain of hand. Attaches directly to TC73/TC78 Includes loop for holding optional stylus. 	
AK4346DW (3rd party) * http://www.ultimacase.cor		Ultima Case Sling/Waistbelt Holster	 Made with durable, easy-care Ballistic Nylon. Buckle swivels to conform to body movements. Easy-in, easy-out access to device for fast-paced scanning. Unique strap design allows holster to be carried either on waist or crossbody. Small pockets on sides for markers, pens, etc. RoHS and REACH compliant. 	
AK4338DW (3rd party) * http://www.ultimacase.com		Ultima Case Holster with Multi- Position Belt Loop	 Durable, easy-care Ballistic Nylon exterior. Multi-position belt loop allows comfortable use while standing or sitting. Bottom vent for quick insertion of device. Large pockets on sides for markers, pens, etc. Easy-in, easy-out access to device for fast-paced scanning. RoHS and REACH compliant. 	

CRD-TC78-WCVC-01	Charge-Only Vehicle Cradle - Wireless Charging	 Device inserts bottom first and is retained by top latch. Uses four mounting screws with AMPS hole pattern. Includes stylus holder (stylus not included) which can be mounted on left or right side of cradle or can be removed if not needed. Optional Stylus (SG-STYLUS-TCX-MTL-03) will fit into holder. Does not support Trigger Handle. Wireless charging only supported on TC78. Not supported on TC73. 	 Wireless Charging Battery (BTR) NGTC5TC7-44MAWC-01) For Charging: Cigarette Lighter Auto Charge Cable (CHG-AUTO-CLA1-01) OR Hard Wired Auto Charge Cable (CHG-AUTO-HWIRE1-01) OR Vehicle Charger Cable for USB I/O Hub and ZQ500/ZQ600 Series Printers (VAM-MPP-VHCH1-01) OR Legacy Zebra Vehicle Cradle Adapter Cable (CBL-TC7X-GFS- 01) OR Lind (Gamber-Johnson) Isolated Power Supply when installed on higher voltage vehicles For Mounting: Windshield Suction Mount (RAM-B- 166U) OR See other RAM or ProClip mounting bracket options below.
3PTY-PCLIP-712310 NOTE: Products sold that do not bear the Zebra brand name are serviced and supported exclusively by their manufacturers in accordance with terms and conditions packaged with the products. Zebra's Limited Warranty does not apply to products that are not Zebra branded, even if packaged or sold with Zebra products. Please contact the manufacturer directly for technical support and customer service.	ProClip Charge-Only Vehicle Cradle (Drop-in Style) with Cigarette Lighter Adapter	 This is a light duty, quick and easy, one handed, top drop in style cradle. Cradle can be used in vertical (portrait) position or landscape mode. Cigarette Lighter Adapter (CLA) cable is included. No other power cables needed. Uses four mounting screws with AMPS hole pattern. 12-24V input, 5V output Does not support Trigger Handle. 	► For Mounting: Windshield Suction Mount (RAM-B- 166U) OR other RAM or ProClip mounting bracket options
3PTY-PCLIP-712354 NOTE: Products sold that do not bear the Zebra brand name are serviced and supported exclusively by their manufacturers in accordance with terms and conditions packaged with the products. Zebra's Limited Warranty does not apply to products that are not Zebra branded, even if packaged or sold with Zebra products. Please contact the manufacturer directly for technical support and customer service.	ProClip Charge-Only Vehicle Cradle with Top Clip and Cigarette Lighter Adapter	 This is a light duty, quick and easy, one handed, cradle which includes a top clip to secure the device in the cradle. Cradle can be used in vertical (portrait) position or landscape mode. Cigarette Lighter Adapter (CLA) cable is included. No other power cables needed. Uses four mounting screws with AMPS hole pattern. 12-24V input, 5V output Does not support Trigger Handle. 	► For Mounting: Windshield Suction Mount (RAM-B- 166U) OR other RAM or ProClip mounting bracket options

3PTY-PCLIP-713310 NOTE: Products sold that do not bear the Zebra brand name are serviced and supported exclusively by their manufacturers in accordance with terms and conditions packaged with the products. Zebra's Limited Warranty does not apply to products that are not Zebra branded, even if packaged or sold with Zebra products. Please contact the manufacturer directly for technical support and customer service.		ProClip Charge-Only Vehicle Cradle (Drop-in Style) with Hard Wired Power Supply	 This is a light duty, quick and easy, one handed, top drop in style cradle. Cradle can be used in vertical (portrait) position or landscape mode. 12/24V hard wired power adapter is included. No other power cables needed. Uses four mounting screws with AMPS hole pattern. 12-24V input, 5V output Does not support Trigger Handle. 	► For Mounting: Windshield Suction Mount (RAM-B- 166U) OR other RAM or ProClip mounting bracket options
various SKUs (3rd party) * http://www.proclipusa.com/cate	A CONVICED TRANSPORT	ProClip Vehicle Cradles	 Available in both non-powered, hard wired and cigarette lighter adapter cable configurations. Versions available with top support arm and lock. Durable cradle design for rugged enterprise use. Cradle provided 15 degree angle in any direction. Allows for portrait and landscape view. AMPS hole pattern for simple wall, pedestal or vehicle dashboard mounting. 	
3PTY-RAM-HOL-ZE17-1U NOTE: Products sold that do not bear the Zebra brand name are serviced and supported exclusively by their manufacturers in accordance with terms and conditions packaged with the products. Zebra's Limited Warranty does not apply to products that are not Zebra branded, even if packaged or sold with Zebra products. Please contact the manufacturer directly for technical support and customer service.		RAM Charge-Only Non-Locking Vehicle Cradle	 Spring-loaded cradle allows easy one handed insertion and removal. Compatible with RAM two-hole AMPS pattern diamond bases that will connect to B and C size ball mounts, allowing for a wide variety of mounting options. Compatible when using optional handstrap. Includes stylus holder (stylus not included) which is fixed mounted on left side of cradle. Optional STYLUS-TCX-MTL-03) will fit into holder. Uses RAM Mount RAM-HOL-ZE17-1U 	For Charging: RAM GDS Modular Charger, see In-Vehicle Power Supplies section below For Mounting: Windshield Suction Mount (RAM-B- 166U) OR Vehicle Cradle RAM mount ball (RAM-B-238U) and additional RAM mount hardware

3PTY-RAM-HOL-ZE17L-1U NOTE: Products sold that do not bear the Zebra brand name are serviced and supported exclusively by their manufacturers in accordance with terms and conditions packaged with the products. Zebra's Limited Warranty does not apply to products that are not Zebra branded, even if packaged or sold with Zebra products. Please contact the manufacturer directly for technical support and customer service.		RAM Charge-Only Locking Vehicle Cradle	 Spring-loaded cradle allows easy one handed insertion and removal. Includes lock. Compatible with RAM two-hole AMPS pattern diamond bases that will connect to B and C size ball mounts, allowing for a wide variety of mounting options. Compatible when using optional handstrap. Includes stylus holder (stylus not included) which is fixed mounted on left side of cradle. Optional Stylus (SG-STYLUS-TCX-MTL-03) will fit into holder. Uses RAM Mount RAM-HOL-ZE17L-1U 	
various SKUs (3rd party) * <u>https://www.rammount.com</u>		RAM Charge-Only Vehicle Cradle	 Spring-loaded cradle allows easy one handed insertion and removal. Compatible with RAM two-hole AMPS pattern diamond bases that will connect to B and C size ball mounts, allowing for a wide variety of mounting options. Compatible when using optional handstrap. Includes stylus holder (stylus not included) which is fixed mounted on left side of cradle. Optional Stylus (SG-STYLUS-TCX-MTL-03) will fit into holder. 	For Charging RAM GDS Modular Charger, see In-Vehicle Power Supplies section below For Mounting ▶ Windshield Suction Mount (RAM- B-166U) OR ▶ see RAM website for other options
Un-Powered Cradles and Hole	ders (passive holders, no char	ging support)		
Part Number	Picture	Description	Notes	Required Items
CRD-TC7NG-NCCD-01		Vehicle Holder	 Holds device in vehicle installations. Spring tension on holder. Provides access to USB-C port on bottom of device allowing device to be charged. Does not support Trigger Handle. 	►For Mounting: Windshield Suction Mount (RAM-B-166U) OR See other RAM or ProClip mounting bracket options below.

various SKUs (3rd party) * <u>http://www.proclipusa.com/cate</u>	egory/zebra	ProClip Vehicle Holders	 Versions available with top support arm and lock. Durable cradle design for rugged enterprise use. Cradles provided 15 degree angle in any direction. Allows for portrait and landscape view. AMPS hole pattern for simple wall, pedestal or vehicle dashboard mounting. 	
RAM-HOL-ZE17-NP-1U (non-locking version) RAM-HOL-ZE17L-NP-1U (locking version) (3rd party) *		RAM Vehicle Holder	 Spring-loaded cradle allows easy one handed insertion and removal. Compatible with RAM two-hole AMPS pattern diamond bases that will connect to B and C size ball mounts, allowing for a wide variety of mounting options. Compatible when using optional handstrap. Includes stylus holder (stylus not included) which is fixed mounted on left side of cradle. Optional Stylus (SG-STYLUS-TCX-MTL-03) will fit into holder. 	For Mounting ▶ Windshield Suction Mount (RAM- B-166U) OR ▶ see RAM website for other options
Vehicle Mounting Hardware				
Part Number	Picture	Description	Notes	Required Items
RAM-B-166U		Vehicle Cradle Windshield Suction Cup Mount	 RAM Twist Lock Suction Cup with Double Socket Arm and Diamond Base Adapter Overall Length: 6.75" Attaches to back of Vehicle Cradles 	
RAM-B-238U		Vehicle Cradle RAM Mount ball	 RAM 2.43" x 1.31" Diamond Ball Base w/ 1" Ball Attaches to back of Vehicle Cradles 	Requires additional RAM hardware to mount vehicle cradle

3PTY-PCLIP-241476	PreClipUSA.com	ProClip Forklift/Vehicle Cradle Clamp Mount - for Pipe/Bar mounting	 Attaches to circular pipes/bars of vehicles/forklifts. Accommodates bars from 3/4" to 1 1/8" diameter (19 to 30 mm). Uses AMPS hole pattern for mounting ProClip cradles like 3PTY-PCLIP-241475. NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
3PTY-PCLIP-241477		Clamp Mount with Backplate - for Pipe/Bar mounting	 Attaches to circular pipes/bars of vehicles/forklifts. Accommodates bars from 3/4" to 1 1/8" diameter (19 to 30 mm). Includes 3PTY-PCLIP-241476 with an attached backplate that uses AMPS hole pattern for mounting vehicle cradles. NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item. 	
3PTY-PCLIP-241478		ProClip Forklift/Vehicle Cradle Clamp Mount - for square frame mounting	 Attaches to square bars of vehicles/forklifts. Clamp is 5.125" x 3.75" and can accommodate bars of vaying thicknesses. 6" long arm on clamp uses AMPS hole pattern for mounting ProClip cradles like 3PTY-PCLIP-241475. 	
3PTY-PCLIP-215500		ProClip Tilt Swivel Mount For TC7X/TC5X Vehicle Cradles	 For mounting Vehicle Cradle on any flat surface. Angles/Tilts 15 degrees Swivels 360 degrees Extends 1 inch / 2.54 cm Base Plate and Face Plate has AMPS hole pattern Weight capacity 25 lbs / 11.34 kgs NOTE: Restricted Product - Must open CPR at http://cpr.zebra.lan (Zebra internal site). Sample devices shall then be provided, and once the customer approves these demo devices, the SKU shall be opened for sale to that customer. Refer to PMB 2756 for details. 	Vehicle Cradle (CRD-TC56 CVCD1-01 or CRD-TC56- UVCD1-01)

This Tilt Swide Mount is made for use with noticels for the wife address

9

-

Page 13 of 23

Company Info:

Document Update date: 6/23/23

	1			.
3PTY-PCLIP-710836		2" tall Pedestai Mounting Kit - Horizontal Adjustment, For TC7X/TC5X Vehicle Cradle	 2 inch Solid-core Aluminum quick- adjust interlocking joint. The round bases provide an industry- standard 4-hole AMPS mounting pattern with approximately 20 degrees of rotation to facilitate the perfect mounting angle and device placement. Adjustable for optimal positioning Weight capacity over 300 lbs NOTE: Restricted Product - Must open CPR at http://cpr.zebra.lan (Zebra internal site). Sample devices shall then be provided, and once the customer approves these demo devices, the SKU shall be opened for sale to that customer. Refer to PMB 2756 for details. 	Vehicle Cradle (CRD-TC56- CVCD1-01 or CRD-TC56- UVCD1-01)
This 2 inch Solid-core Aluminum i	edestal Mountains with a suith Mou		 ◆ 4 inch Solid-core Aluminum quick- adjust interlocking joints. ◆ Mount also features a 2 inch 90- degree offset extension rod to enable both horizontal and vertical adjustment to achieve optimal device/cradle 	
3PTY-PCLIP-710834 Office:	ip usa, Ma	ProClip 4" tall Pedestal Mounting Kit For TC7X/TC5X Vehicle Cradles - Horizontal & Vertical Adjustment	 positioning. AMPS hole pattern in mount bases Quick and easy installation Adjustable for optimal positioning Weight capacity over 300 lbs NOTE: Restricted Product - Must open CPR at http://cpr.zebra.lan (Zebra internal site). Sample devices shall then be provided, and once the customer approves these demo devices, the SKU shall be opened for sale to that customer. Refer to PMB 2756 for details. 	Vehicle Cradle (CRD-TC56- CVCD1-01 or CRD-TC56- UVCD1-01)
This 4 inch Solid-core Aluminu	n Pedestal Moore the uncertainty of the provide a saf	er and more enjoyable driving experience.	 4 inch Solid-core Aluminum quick- adjust interlocking joints. Mount also features a 2 inch Horizontal extension rod between mount bases AMPS hole pattern in mount bases 	
3PTY-PCLIP-710835		4" tall Pedestal Mounting Kit For TC7X/TC5X Vehicle Cradles - Horizontal Adjustment	 Quick and easy installation Adjustable for optimal positioning Weight capacity over 300 lbs NOTE: Restricted Product - Must open CPR at http://cpr.zebra.lan (Zebra internal site). Sample devices shall then be provided, and once the customer approves these demo 	Vehicle Cradle (CRD-TC56- CVCD1-01 or CRD-TC56- UVCD1-01)
Office: Pr	pc	ny Info:	devices, the SKU shall be opened for sale to that customer. Refer to PMB 2756 for details.	

This 4 inch Solid-core Aluminum Pedestal Mount come with quick provide a safer and more enjoyable driving experience.

			Standard Duty mount is designed to be used in smooth-riding vehicles and	
3PTY-PCLIP-241479		ProClip Standard Duty 5" Pedestal Mount	areas with low risk of external contact. ► Length of arm assembly is 5". ► Uses AMPS hole pattern for mounting ProClip cradles like CRD-TC56-CVCD2- 02. ► NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	Vehicle Cradle (CRD-TC56- CVCD1-01 or CRD-TC56- UVCD1-01)
3PTY-PCLIP-710837		ProClip 6" tall Pedestal Mounting Kit - Horizonal & Vertical Adjustment, For TC7X/TC5X Vehicle Cradles	 ▶ 6 inch Solid-core Aluminum quick- adjust interlocking joint. ▶ The round bases provide an industry- standard 4-hole AMPS mounting pattern with approximately 20 degrees of rotation to facilitate the perfect mounting angle and device placement. ▶ Adjustable for optimal positioning ▶ Weight capacity over 300 lbs ▶ NOTE: Restricted Product - Must open CPR at http://cpr.zebra.lan (Zebra internal site). Sample devices shall then be provided, and once the customer approves these demo devices, the SKU shall be opened for sale to that customer. Refer to PMB 2756 for details. 	Vehicle Cradle (CRD-TC56- CVCD1-01 or CRD-TC56- UVCD1-01)
3PTY-PCLIP-710838		ProClip 8" tall Pedestal Mounting Kit - Horizontal Adjustment,For TC7X/TC5X Vehicle Cradles	 ▶ 8 inch Solid-core Aluminum quick- adjust interlocking joint. ▶ The round bases provide an industry- standard 4-hole AMPS mounting pattern with approximately 20 degrees of rotation to facilitate the perfect mounting angle and device placement. ▶ Adjustable for optimal positioning ▶ Weight capacity over 300 lbs ▶ NOTE: Restricted Product - Must open CPR at http://cpr.zebra.lan (Zebra internal site). Sample devices shall then be provided, and once the customer approves these demo devices, the SKU shall be opened for sale to that customer. Refer to PMB 2756 for details. 	Vehicle Cradle (CRD-TC56- CVCD1-01 or CRD-TC56- UVCD1-01)
Misc	l 			
Part Number	Picture	Description	Notes	Required Items

SG-STYLUS-TCX-MTL-03 (pack of 3)		Fiber Tipped Stylus	 Black Passive Stylus with Zebra logo 5" length Heavy duty - made from stainless steel and brass. No plastic parts - real pen feel. Can be used in rain. Micro-Knit Hybrid Mesh Fiber Tip provides silent, smooth gliding use. Big improvement over rubber tipped o plastic tipped stylus. Compatible with all capacitive touch screen devices. Can be tethered to device using SG- TC5NGTC7NG-TETHR-03. 			
SG-TC5NGTC7NG-TETHR-03 (pack of 3)		Tether for Stylus	 String type tether prevents loss of stylus NOTE: Other Zebra coiled tethers are not recommended for use with TC73/TC78 as they may interfere with other accessories. NOTE: This tether is recommended when using Fiber Tipped Stylus (SG-STYLUS-TCX-MTL-03). Other tethers may not fit easily through the tether loop hole on the stylus. 			
SG-NGTC7-SCRNP-03 (pack of 3)		Screen Protectors	 Tempered glass Includes alcohol wipes, cleaning cloth and tools needed for screen protector installation. 			
	Headset/Audio Accessories					
Wired Headsets and Audio Accessories NOTE: Wired headsets with 2.5mm or 3.5mm jacks are not supported on TC73/TC78 devices since they do not include a headset jack.						
Part Number	Picture	Description	Notes	Required Items		
HDST-USBC-PTT1-01		PTT Headset (USB-C connector)	 For Push-To-Talk (PTT) applications. Compatible with Zebra PTT Express and PTT Pro. Connects to USB-C port on device. Rotating earpiece allows for right or left ear configuration. Provides PTT button, volume up/volume down buttons. Cable length is 32 in. (81 cm) mono with microphone includes clip for attaching PTT button to clothing. 			

EMC Product Line - TC73/TC78 TAG

Bluetooth Headsets and Audio Accessories NOTE: Bluetooth headsets with PTT function not supported by Zebra PTT Express application. Check Zebra WFC Central Client app Release Notes to verify compatibility.				
Part Number	Picture	Description	Notes	Required Items
See HS2100-HS3100 Accessories Document	5	HS3100 Rugged Bluetooth Headset for VDP applications	 HD Voice, also known as Wide Band Audio, brings incredible audio clarity Built to handle the everyday inevitable drops Dustproof, sprayproof and waterproof Ready for the freezer and outdoor subzero temperatures Feather-light for extraordinary comfort Noise cancellation tuned for VDP (voice directed picking) applications. Not designed for the agressive noise cancellation required for VoIP or voice scandards and will result with audio being quieter at the far end and delivering more noise. Swap batteries on the fly — without losing the Bluetooth connection Split-second tap-to-pair simplicity using NFC. Detachable swivel boom minimizes costs. Swiveling boom mutes microphone allowing uses to prevent voice pick applications. User-replaceable pads and windscreens maximize comfort and hygiene 15 hours of battery power 	See HS2100/HS3100 Accessories Document for headset accessories
various Bluetooth models B550-XT B350-XT C400-XT C300-XT (3rd party) * http://www.blueparrott.com		BlueParrott Bluetooth Headsets	 Various Bluetooth models available with options that include: Blocking out 96% of background noise Over 24 hours of talk time NFC Tap to Pair capable Bluetooth wireless range capable up to 300 ft. Convertible wearing options: over the head, behind the neck. See BlueParrot site for model specific options. 	
APTT1 (3rd party) *		Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)	 Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). Includes clip for attaching device to closthing for lapel speaker/mic usage. Features several buttons which the application developers can assign to different functions. Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. Device is ruggedized, MIL-STD 810G and IP67. Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. Includes 3.5mm headset jack allowing headphones to be connected for 	
https://www.aina-wireless.com/			keeping conversations more private. ► Can be easily paired to mobile computer using NFC tap-to-pair.	

BTR-155			 ▶Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Includes clip for attaching device to better the provide t	
(3rd party) *		Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)	closthing for lapel speaker/mic usage. > Rugged wireless speaker microphone IP55. > Allows cable-free movement > Familiar speaker microphone functions; PTT and volume buttons > Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. > LED status indication > High speaker volume > Includes: - Savox RSM - Modular Wired earpiece	
https://www.savoxaccessories.com			- Wall Charger - USB Cable - Quick Start Guide - Carrying Strap	
various (3rd party) * http://stonemountainItd.com	A Contraction of the second seco	Stone Mountain BluSkye Bluetooth Remote Speaker Mic (RSM)	 Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). Device is ruggedized, MIL-STD 810G and IP68. 	
Power Cords/Power Sup	plies			
AC Cords and Power Supplie	25			
Part Number	Picture	Description	Notes	Required Items
CBL-DC-388A1-01		DC Power Cord	 Used to power Single Slot Cradles and 4-Slot Battery Chargers when using Level VI Efficiency power supply (PWR-BGA12V50W0WW) Cable length is 1.8 meters NOTE: All TC73/TC78 Cradles include this cable. 	
CBL-DC-388A2-01		DC Power Cord for Workstation Cradles	 Used along with Power Supply PWR- BGA12V50W0WW to power Workstation Cradle (CRD-NTC7X- 1SNWS-01). Barrel Jack connector is straight and ferrite is in a different location vs. L- shaped connector on CBL-DC-388A1- 01. Cable length is 1.8 meters NOTE: CBL-DC-388A1-01 may also be used with Workstation Cradles, but CBL-DC-388A2-01 is recommended to provide easier installation of peripheral cables and the cradle's port cover. 	

PWR-BGA12V50W0WW		Power Supply	 Replaces PWRS-14000-148R Used to power Single Slot Cradle and 4-Slot Battery Charger 100-240 VAC,12VDC,3.33A Level VI Efficiency rated NOTE: All TC73/TC78 Cradles include this power supply. 	 DC Power Cord (CBL-DC- 388A1-01) AC Line Cord (23844-00-00F or country specific version)
KIT-PWR-12V50W		Power Supply Kit	► Includes Power Supply (PWR- BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01)	► AC Line Cord (23844-00-00F or country specific version)
CBL-DC-381A1-01		DC Power Cord	 Used to power 5-Slot ShareCradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) NOTE: All TC73/TC78 Multi-Slot ShareCradles include this cable. This cable does not include the black extension release latch which is not required when used on Multi-Slot ShareCradles. 	
CBL-DC-382A1-01		DC Power Cord	 Used to power 5-Slot ShareCradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) Cable has black extension tab for releasing the cable from the back of the cradle. This isn't required when using Multi-Slot ShareCradles. CBL-DC-381A1-01 is normally used with TC73/TC78 multi-device cradles. 	
CBL-DC-523A1-01		2-Way DC Y Power Cord	► Used to power two 4-Slot Battery Chargers from one Power Supply (PWR- BGA12V108W0WW)	
PWR-BGA12V108W0WW	Total Social Social	Power Supply	 Used to power 5-Slot ShareCradles of two 4-Slot Spare Battery Chargers 9A, 108W Level VI Efficiency rated NOTE: All TC73/TC78 Cradles include this power supply. 	 ▶ DC Line Cord (CBL-DC- 381A1-01 or CBL-DC-523A1- 01) ▶ AC Line Cord (23844-00-00F or country specific version)
23844-00-00R		AC Line Cord	 Used to power Cradles. This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries. 	
PWR-WUA5V12W0US (US plug style) PWR-WUA5V12W0GB (UK plug style) PWR-WUA5V12W0EU (EU plug style) PWR-WUA5V12W0AU (Australia plug style) PWR-WUA5V12W0CN (China plug style) PWR-WUA5V12W0IN (India plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0BR (Brazil plug style) PWR-WUA5V12W0BR		USB Power Supply	 Used with USB-C Cable (CBL-TC5X-USBC2A-01) to charge device. Provides higher current (2.5A) for faster charging 100-240 VAC, 5 V, 2.5 A 	
In-Vehicle Power Supplies				

EMC Product Line - TC73/TC78 TAG

NOTE: Items highlighted in grey may not be orderable/available

Part Number	Picture	Description	Notes	Required Items
CHG-AUTO-USB1-01 CHG-AUTO-USB1-BR (for Brazil)		USB Cigarette Lighter Adapter	 ► Used with USB-C Cable (CBL-TC5X- USBC2A-01) to charge device. ► Includes two USB A ports providing higher current (2.5A) for faster charging 	
CHG-AUTO-CLA1-01		Cigarette Lighter Auto Charger Cable for Vehicle Cradle	 ► 12/24V ► Includes tab on Barrel jack end for ensuring a reliable connection to Vehicle Cradle (CRD-TC78-WCVC-01). ► Only compatible with Vehicle Cradle (CRD-TC78-WCVC-01) 	
CHG-AUTO-HWIRE1-01		Hard Wired Auto Charger Cable for USB I/O Hub	 12/24V Includes tab on Barrel jack end for ensuring a reliable connection to Vehicle Cradle (CRD-TC78-WCVC-01). Bare wire end connects directly to vehicle power source. Only compatible with Vehicle Cradle (CRD-TC78-WCVC-01) Approximate cable length is 13 ft. 	
CBL-TC7X-GFS-01		Zebra Legacy Vehicle Cradle Power Adapter Cable	 Allows Vehicle Cradle (CRD-TC78-WCVC-01) to use power cables from legacy Zebra device vehicle cradles including: MC5x/MC6x, MC7x, MC9x-Brick, MC9x-Short, or MC95 which use cable SKUs 25-128973-01R, 25-61987-01R, or 25-128974-01R. Cable length is 11.5" NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this cable. 	
ADPCBL-TC7X-USPS		Honeywell Legacy Vehicle Cradle Power Adapter Cable	 Allows Vehicle Cradle (CRD-TC78-WCVC-01) to use power cables from legacy Honeywell vehicle cradles providing 12V - typically Honeywell 99ex. Cable length is about 12". NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this cable. 	

_				
VAM-MPP-VHCH1-01 (CPR required for use with TC73/TC78)		Vehicle Charger Cable for Vehicle Cradle and ZQ500/ZQ600 Series Printers	 Charger with charge both the Vehicle Cradle (CRD-TC78-WCVC-01) a ZQ500 or ZQ600 series printer. Includes the following: Power Supply (P1093358) which has square locking connector and one USB-A port which can be used to charge an additional device. cable for charging Vehicle Cradle (CRD-TC78-WCVC-01) (includes tab on Barrel jack end for ensuring a reliable connection to the cradle) and ZQ500/ZQ600 printer cable for charging legacy TC7X Charging Cable Cup, Serial/Charge Cable, or USB/Charge Cable Cups and ZQ500/ZQ600 printer - will not be used with TC73/TC78. Cigarette Lighter Adapter power cord Hard Wired (bare wire) power cord NOTE: This charging solution has not been officially validated with the TC73/TC78. Please submit a CPR at http://cpr.zebra.lan (Zebra internal site) if you would like to use this cable with the TC73/TC78. 	
7300-0466 (12-32 VDC input)				
(12-32 VDC input) 7300-0467 (20-60 VDC input)			► Typically used when powering Vehicle Cradle (CRD-TC78-WCVC-01) from	
7300-0418 (72-110 VDC input)		Lind 12V Isoloated Power Supply for Vehicle Cradle	higher voltage vehicles. ► Provides 12V DC output required by cradle.	
Gamber Johnson (3rd party) *	~			
http://www.gamberjohnson.com	<u>n</u>			
3PTY-RAMGDSCHARGEM55V7B1U (10-30V input range)				
SPTY-RAM-GDSCHARGEM55V8BU (30-64V input range) NOTE: Products sold that do not bear the Zebra brand name are serviced and supported exclusively by their manufacturers in accordance with terms and conditions packaged with the products. Zebra's Limited Warranty does not apply to products that are not Zebra branded, even if packaged or sold with Zebra products. Please contact the manufacture directly for technical support and customer service.		RAM GDS Modular Charger	 Used to power RAM Vehicle Cradles Charger includes: USB Type-A male connection to 5.5mm DC connector adapter cable Hard wired power adapter, USB Type-A female connector; 10-30V or 30-64V input range, 5V output Eases device upgrades by avoiding rewiring, just unplug power connector and attach new charger components 	
RAM-GDS-CAB-USBA-DC90-1U (plugs into existing USB-A port, only includes USB-A to 5.5mm DC connector adapter cable) RAM-GDS-CHARGE-M55-V7B1U (for 10-30V vehicles)		RAM GDS Modular	 Used to power RAM Vehicle Cradles Chargers includes: USB Type-A male connection to 5.5mm DC connector adapter cable Hard wired power adapter, USB 	
RAM-GDS-CHARGE-M55-V8BU (for 30-64V vehicles) (3rd party) *		Chargers	Type-A female connector; 10-30V or 30V-64V input range, 5V output ▶ When upgrading devices, avoid rewiring by unplugging power connector and attaching new charger	
https://www.rammount.com			components	
Batteries				

EMC Product Line - TC73/TC78 TAG

Part Number	Picture	Description	Notes	Required Items
BTRY-NGTC5TC7-44MA-01 (single) BTRY-NGTC5TC7-44MA-10 (pack of 10) BTRY-NGTC5TC7-44MA-BR (single - for use in Brazil) BTRY-NGTC5TC7-44MA-IN (single - for use in India)		Spare 1X Standard Capacity Battery with PowerPrecision Plus (4400 mAh)	 Designed, manufactured & tested to meet rigorous controls & standards Premium-grade cells with higher capacity & longer life cycle Designed to help prevent overcharging & electrical shock Strong & robust housing for optimal performance & durability Information available: Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device. Advanced State of Health (highly accurate end-of-life prediction) Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency). 	
BTRY-NGTC5TC7-44MABLE-01	*	Spare 1X Standard Capacity Battery with PowerPrecision Plus (4400 mAh) and BLE beacon	 Designed, manufactured & tested to meet rigorous controls & standards Premium-grade cells with higher capacity & longer life cycle Designed to help prevent overcharging & electrical shock Strong & robust housing for optimal performance & durability Information available: Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device. Advanced State of Health (highly accurate end-of-life prediction) Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency). Includes Bluetooth beacon allowing device to be located while powered off using solutions like Zebra Device Tracker. Once the battery can no longer powe the device the BLE beacon in the battery will continue to beacon for about 7-10 days. Battery purchase is eligible for discounted Device Tracker 1-year or 3-year subscription. See PMB 10837 for details. 	► Typically purchased along with a Device Tracker 1-year or 3-year subscription. Battery is eligible for a discounted Device Tracker subscription: SW-BLE-DT-SP-1YR (1 year) or SW-BLE-DT-SP-3YR (3 year) See PMB 10837 for details.

BTRY-NGTC5TC7-44MAWC-01	(2)	Spare 1X Standard Capacity Battery with PowerPrecision Plus (4400 mAh) and Wireless Charging	 Designed, manufactured & tested to meet rigorous controls & standards Premium-grade cells with higher capacity & longer life cycle Designed to help prevent overcharging & electrical shock Strong & robust housing for optimal performance & durability Information available: Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device. Advanced State of Health (highly accurate end-of-life prediction) Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency). Includes support for wireless charging only supported on TC78. Not supported on TC73. 	
BTRY-NGTC5TC7-PYMT		1X Standard Capacity Battery with PowerPrecision Plus (4400 mAh) and Payment Support	 Battery includes slot for integration with PD20 payment device. Includes two Torx T5 screws to secure PD20 in Battery. Compatible with Soft Holster Not compatible with: hand strap other snap-on accessories vehicle cradles Workstation Connect cradle Spare Battery Chargers - battery must be charged while in device. Designed, manufactured & tested to meet rigorous controls & standards Premium-grade cells with higher capacity & longer life cycle Designed to help prevent overcharging & electrical shock Strong & robust housing for optimal performance & durability Information available: Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real- time usage patterns of the device. Advanced State of Health (highly accurate end-of-life prediction) Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency). 	
BTRY-NGTC5TC7-66MA-01 BTRY-NGTC5TC7-66MA-BR (for use in Brazil) BTRY-NGTC5TC7-66MA-IN (for use in India)		Spare 1.5X Extended Capacity Battery with PowerPrecision Plus (6600 mAh)	 Designed, manufactured & tested to meet rigorous controls & standards Premium-grade cells with higher capacity & longer life cycle Designed to help prevent overcharging & electrical shock Strong & robust housing for optimal performance & durability Information available: Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device. Advanced State of Health (highly accurate end-of-life prediction) Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency). 	